



| RIF. | Q.TY | DESCRIPTION | DRAWING |
|------|------|---|-------------|
| 1 | 1 | BASE 4M XT WITH SPACERS FOR RASPBERRY PI B+/3/4 AND ODROID C1/C1+ | 2_050_00025 |
| 2 | 1 | MODULAR HOOK LONG | 2_250_00072 |
| 3 | 1 | BODY 4M53-C XTS ODROID C4 | 2_050_00038 |
| 4 | 1 | PANEL 4M WITHOUT FRAME | 2_250_00088 |
| 5 | 2 | SCREW d 2.9 X 6.5 TC+ TRUNK-POINT | 8_100_00003 |

| General Tolerance UNI EN 22768/1 Media (m) | | | | |
|--|------------------|----------------------|----------------|------------------|
| from 0.5 to 3 | from 3 to 6 | from 6 to 30 | from 30 to 120 | from 120 to 400 |
| ± 0.1 | ± 0.1 | ± 0.2 | ± 0.3 | ± 0.5 |
| Scale: 1 : 1 | Sheet nr.: 1 / 1 | Drawn: F.E. | Checked: R.N. | Date: 13/07/2020 |
| Material: | | Weight: | | Cod. Mold: |
| Description: | | KIT 4M XTS Odroid C4 | | |
| Drawing nr. 3_050_00039 | | | | Rev. 00 |

RESERVED PROPERTY: The present drawing cannot be reproduced or communicated to 3rd parties, even partially, without the authorization of ITALTRONIC Srl. Italtronic reserves to protect its own rights according to the law.