



General information:

- Workpiece zero point for mechanical processing
- Minimum recommended radius for machining = R1.0 mm
- Mounting rail like EN 60715: TH 35-7.5 or TH 35-15
- Recommended PCB outline on www.italtronic.com

RIF.	Q.TY	DRAWING	DESCRIPTION
1	1	2_050_00056	BASE MODULBOX XT-XTS 4M ROCK 4 SE
2	1	2_050_00054	BODY 4M53-C XTS ROCK 4 SE
3	1	2_250_00072	HOOK FOR MODULBOX XT-XTS
4	1	2_250_00088	PANEL MODULBOX WITHOUT FRAME 4M
5	2	8_100_00003	SCREW d 2.9 X 6.5 TC+ TRUNK-POINT

General Tolerance UNI EN 22768/1 Media (m)						Sheet:
from 0.5 to 3	from 3 to 6	from 6 to 30	from 30 to 120	from 120 to 400		1
± 0.1	± 0.1	± 0.2	± 0.3	± 0.5		
Scale:	IM:	Drawn:	Checked:	Date:	Material:	Process:
1:1	--	M.S.	R.N.	14/12/2023		
	The present drawing cannot be reproduced or communicated to 3rd parties, even partially, without the authorization of Italtronic. Italtronic reserves the right to protect its copyrights according to the law.		Replaces the:	Derived from:	Weight:	Cod. Mold:
Dimension in mm			--	--	gr	--

 enclosures for electronics italtronic.com	Description:		Rev.:
	KIT CONTENITORE MODULBOX XTS 4M ROCK 4 SE KIT ENCLOSURE MODULBOX XTS 4M ROCK 4 SE Drawing nr.: 3_050_00047		